

Description

ACU-MP2 is a composition of an ATS that safely and easily controls ATS with a microprocessor containing a lot of functions in it instead of extra units that only simply manipulate ATS.



Key Features

- Detects 3P of commercial power and indicates absent phase.
- Indicates states of commercial/generator power and transfer state.
- Anti burnt down of ATS coil (Output contact only for 1sec)
- Test mode included
- Contains engine start contact when commercial power has fault
- Occupies less attaching space and shorten the working time

Mechanical Features



- AUTO Function: while commercial power or generator power is being input, switch is transferred to normal power if there occurs a broken power.
- Anti burnt down of ATS coil: buzzer alarms and transfer indication lamp blinks when transfer signal of ATS is not received after transfer output is output for a sec during manual and automatic operation.
- TEST MODE function is a function to test one cycle making commercial power back from outage and operating engine generator and inserted to generator power and then to commercial power

Specifications

- Commercial Power Input: 3P4W, 220/380Vac, 50/60Hz
- Generator Power Input: 1P, 220Vac, 50/60Hz
- Transfer Output Contact Capacity: 250Vac, 5A(Dry Contact)
- Assistant Contact Capacity of Commercial Power Fault: 250Vac, 10A(Dry Contact)


Easy

Digital


Design

Yes

Connection Circuit



Dimension(mm)



Mi<u>scellaneous</u>

Weight(kg): 1

 Case of Bottom : Aluminum(heatpreventing cover)

Case of Top : Steel

Input Fuse : 3A, 250V, Φ5.2-20L

Output Fuse : 10A, 250V, Φ5.2-20L



Engine generator control enterprise Fax: 8: Fax: 8: Email:

Tel: 82-32-677-9806 Fax: 82-32-677-9807 Email: sales@egcon.co.kr

Web: www.egcon.o.kr